Technical belt data sheet

Nonex EM 8/2 00+03 light blue AS FG AM



Article code 572780

General information						
Product group	Synthetic belts	Synthetic belts				
Market segment	General food, Fruit & v	General food, Fruit & vegetable, Bakery				
Main features	Antistatic, Foodgrade,	Antistatic, Foodgrade, Anti-microbial				
Belt support	Slider bed, Rollers, Fla	Slider bed, Rollers, Flat				
Belt construction						
Fabric tension layer	polyester	stable	2-ply			
Topside	Nonex PVC	smooth	light blue			
Bottomside	PUR	impregnation	light blue			
Characteristics						
Foodgrade (FG)	yes, according: EC 19	yes, according: EC 1935/2004 (and amendments); food contact surface FDA				
Antistatic (AS)	yes					
High conductive (HC)	no	no				
Flame retardant (FR)	no	no				
ATEX approval	no	no				

Technical belt data

Hardness topside according to ISO 868 65A shore Force at 1% elongation according to ISO 21181 8.0 N/mm 44.80 lbs./m Belt thickness internal AB method KV.002 1.60 mm 0.063 in. Weight internal AB method KV.004 1.80 kg/m² 0.369 lbs./m Thickness top cover 0.30 mm 0.012 in. Temperature range -15 to 80 °C 5 to 176 °F Temperature range short -15 to 100 °C 5 to 212 °F Min. pulley diameter flexing 20.0 mm 0.787 in. Min. pulley diameter back flexing 30.0 mm 1.181 in. Standard belt width 2020 mm 79.53 in.						
Belt thicknessinternal AB method KV.0021.60mm0.063in.Weightinternal AB method KV.0041.80kg/m²0.369lbs./ft.Thickness top cover0.30mm0.012in.Temperature range-15 to 80°C5 to 176°FTemperature range short-15 to 100°C5 to 212°FMin. pulley diameter flexing20.0mm0.787in.Standard belt width2020mm79.53in.	Hardness topside	according to ISO 868	65A	shore		
Weightinternal AB method KV.0041.80kg/m²0.369lbs./ft.Thickness top cover0.30mm0.012in.Temperature range-15 to 80°C5 to 176°FTemperature range short-15 to 100°C5 to 212°FMin. pulley diameter flexing20.0mm0.787in.Min. pulley diameter back flexing30.0mm1.181in.Standard belt width2020mm79.53in.	Force at 1% elongation	according to ISO 21181	8.0	N/mm	44.80	lbs./in.
Thickness top cover0.30mm0.012in.Temperature range-15 to 80°C5 to 176°FTemperature range short-15 to 100°C5 to 212°FMin. pulley diameter flexing20.0mm0.787in.Min. pulley diameter back flexing30.0mm1.181in.Standard belt width2020mm79.53in.	Belt thickness	internal AB method KV.002	1.60	mm	0.063	in.
Temperature range-15 to 80°C5 to 176°FTemperature range short-15 to 100°C5 to 212°FMin. pulley diameter flexing20.0mm0.787in.Min. pulley diameter back flexing30.0mm1.181in.Standard belt width2020mm79.53in.	Weight	internal AB method KV.004	1.80	kg/m²	0.369	lbs./ft. ²
Temperature range short-15 to 100°C5 to 212°FMin. pulley diameter flexing20.0mm0.787in.Min. pulley diameter back flexing30.0mm1.181in.Standard belt width2020mm79.53in.	Thickness top cover		0.30	mm	0.012	in.
Min. pulley diameter flexing20.0mm0.787in.Min. pulley diameter back flexing30.0mm1.181in.Standard belt width2020mm79.53in.	Temperature range		-15 to 80	°C	5 to 176	°F
Min. pulley diameter back flexing30.0mm1.181in.Standard belt width2020mm79.53in.	Temperature range short		-15 to 100	°C	5 to 212	°F
Standard belt width 2020 mm 79.53 in.	Min. pulley diameter flexing		20.0	mm	0.787	in.
	Min. pulley diameter back flexing		30.0	mm	1.181	in.
Maximum belt width 2020 mm 79.53 in.	Standard belt width		2020	mm	79.53	in.
	Maximum belt width		2020	mm	79.53	in.

Endless instructions

Hot splicing is always preferable. Cold splicing can only be done when the belt is exposed to normal temperatures and the humidity is not excessive. For the working method, consult the splice information and the equipment literature. Apply the recommended splice as indicated in the separate information.

Additional information

The information applies at approx. 20°C (68°F). Keep the belt tension to a minimum for maximum belt and conveyor life. Stated is the belt temperature. The allowable product temperature may vary.

The pulley diameters are valid for a hot spliced belt and at the indicated belt force. Depending on the splice and working conditions (e.g. temperature), different pulley diameters may be possible or necessary. When fasteners are used the minimum diameters are increased by approx. 50%.

Consult our specialists for available profiles and accessories.

Because of continuous development, the presented data is subject to alteration. This data replaces that included in previous publications. Ammeraal Beltech excludes any liability for the incorrect use of the above stated information. Subject to the general terms and conditions of sale and delivery, as applied by its operating companies, are all activities performed and services rendered by Ammeraal Beltech.

Product information

Food Statement



Introduction

The framework Regulation EC 1935/2004 Food Contact of the European Parliament lays down regulations on materials and articles intended to come into contact with food. Belonging Regulation EU 10/2011 is a specific measure within the meaning of Article 5 of Regulation EC 1935/2004 and establishes specific requirements for the manufacture and marketing of plastic materials intended to come into contact with



food. Regulation EU 10/2011 is also applicable to printing inks, adhesives or coatings, but does not apply to rubber and silicones. Principle is that food contact materials should be safe and should not transfer their components into the foodstuff (migration) in unacceptable quantities. The EU legislation for food contact materials is based on positive lists of the substances and maximum limits of migration to food. Only positive list substances may be used for manufacturing of food contact plastics.

Statement

Ammeraal Beltech herewith declares that the following mentioned belt type is in compliance with Framework Regulation EC 1935/2004 – which replaces the former Directives 89/109/EEC and 80/590/EEC – and belonging Regulation EU 10/2011 (with amendments) – which replaces former Specific Directives 2002/72/EC and 90/128/EEC (with amendments).

Article code Belt construction

» 572780

Nonex EM 8/2 00+03 light blue AS FG AM

For conveying:

All kind of foodstuffs

Issue date December 2019

Head office Ammeraal Beltech Group Comeniusstraat 8, 1817 MS Alkmaar P.O. Box 38, 1700 AA Heerhugowaard The Netherlands **Product information**

Food Statement FDA



Introduction

The Food and Drug Administration (hereafter called FDA) of the Public Health Service of the Department of Health, Education and Welfare, established in Washington DC 20204, United States of America, is the world's best known authority involved in consumer protection in respect of potential



detrimental influences, which could be caused by any inclusion of substances or ingredients of an unacceptable nature in foodstuffs and confectionery. The FDA have prepared a review 'Title 21: Code of Federal Regulations' in respect of their approval of the raw materials in a processed or finished state, and also specified the conditions under which the approval is valid.

Statement

Ammeraal Beltech herewith declares that the cover of the following belt type meets the requirements mentioned in Title 21: Code of Federal Regulations, issued by the FDA

Article code	Belt construction	
» 572780	Nonex EM 8/2 00+03 light blue AS FG AM	
According to paragraph:		
175.300 (resinous and polymeric coatings)		
178.2010 (antioxidants and/or stabilizers for polymers)		
178.3740 (plasticizers in polymeric substances)		

for all wrapped and unwrapped foodstuffs

Issue date December 2019

Head office Ammeraal Beltech Group Comeniusstraat 8, 1817 MS Alkmaar P.O. Box 38, 1700 AA Heerhugowaard The Netherlands