Technical belt data sheet

## Nonex EM 8/2 00+A18 white AS FG



#### Article code 589609

General information	
Product group	Synthetic belts
Market segment	General food
Main features	Antistatic, Foodgrade
Belt support	Slider bed, Rollers, Flat

Belt construction						
Fabric tension layer	polyester	stable	2-ply			
Topside	Nonex PVC	A18 Fine square profile	white			
Bottomside	fabric	impregnation	natural			

Characteristics				
Foodgrade (FG)	yes, food contact surface according FDA			
Antistatic (AS)	yes			
High conductive (HC)	no			
Flame retardant (FR)	no			
ATEX approval	no			

Technical belt data								
Hardness topside	according to ISO 868	70A	shore					
Force at 1% elongation	according to ISO 21181	8.0	N/mm	44.80	lbs./in.			
Belt thickness	internal AB method KV.002	2.30	mm	0.091	in.			
Weight	internal AB method KV.004	2.10	kg/m²	0.430	lbs./ft.2			
Thickness top cover		0.80	mm	0.031	in.			
Temperature range		-10 to 80	°C	14 to 176	°F			
Temperature range short		-10 to 100	°C	14 to 212	°F			
Min. pulley diameter flexing		40.0	mm	1.575	in.			
Min. pulley diameter back flexing		70.0	mm	2.756	in.			
Standard belt width		2000	mm	78.74	in.			
Maximum belt width		2000	mm	78.74	in.			

### **Endless instructions**

Hot splicing is always preferable. Cold splicing can only be done when the belt is exposed to normal temperatures and the humidity is not excessive. For the working method, consult the splice information and the equipment literature. Apply the recommended splice as indicated in the separate information.

### **Additional information**

The information applies at approx. 20°C (68°F). Keep the belt tension to a minimum for maximum belt and conveyor life. Stated is the belt temperature. The allowable product temperature may vary.

The pulley diameters are valid for a hot spliced belt and at the indicated belt force. Depending on the splice and working conditions (e.g. temperature), different pulley diameters may be possible or necessary. When fasteners are used the minimum diameters are increased by approx. 50%.

Consult our specialists for available profiles and accessories.

Because of continuous development, the presented data is subject to alteration. This data replaces that included in previous publications. Ammeraal Beltech excludes any liability for the incorrect use of the above stated information. Subject to the general terms and conditions of sale and delivery, as applied by its operating companies, are all activities performed and services rendered by Ammeraal Beltech.

© Ammeraal Beltech Printed: January 20, 2021 Edited:

Product information

# Food Statement FDA



## Introduction

The Food and Drug Administration (hereafter called FDA) of the Public Health Service of the Department of Health, Education and Welfare, established in Washington DC 20204, United States of America, is the world's best known authority involved in consumer protection in respect of potential detrimental influences, which could be caused by any inclusion of substances or ingredients of an unacceptable nature in foodstuffs and confectionery. The FDA have prepared a review 'Title 21: Code of Federal Regulations' in respect of their approval of the raw materials in a processed or finished state, and also specified the conditions under which the approval is valid.

### Statement

Ammeraal Beltech herewith declares that the cover of the following belt type meets the requirements mentioned in Title 21: Code of Federal Regulations, issued by the FDA

### Article code Belt construction

» 589609 Nonex EM 8/2 0+A18 white AS FG

According to paragraph: 175.300 (resinous and polymeric coatings)

for all wrapped and unwrapped foodstuffs

Issued: May 2016