

Nonex EM 10/2 00+A18 white AS FG

Article code 589711

General information

Product group	Synthetic belts		
Market segment	General food		
Main features	Antistatic, Foodgrade		
Belt support	Slider bed, Rollers, Flat		

Belt construction

Fabric tension layer	Polyester	stable	2-ply
Topside	Nonex PVC	A18 Fine square profile	white
Bottomside	Ropanol PUR	impregnation	natural

Characteristics

Foodgrade (FG)	yes, food contact surface according FDA
Antistatic (AS)	yes, in accordance with ISO 21178
High conductive (HC)	no
Flame retardant (FR)	no
ATEX approval	no

Technical belt data

Hardness topside	according to ISO 868	70A	shore		
Force at 1% elongation	according to ISO 21181	10.0	N/mm	56.00	lbs./in.
Belt thickness	internal AB method KV.002	3.00	mm	0.118	in.
Weight	internal AB method KV.004	3.20	kg/m ²	0.655	lbs./ft. ²
Thickness top cover		1.20	mm	0.047	in.
Temperature range		-15 to 90	°C	5 to 194	°F
Temperature range short		-15 to 100	°C	5 to 212	°F
Min. pulley diameter flexing		50.0	mm	1.969	in.
Min. pulley diameter back flexing		80.0	mm	3.150	in.
Standard belt width		2000	mm	78.74	in.
Maximum belt width		3000	mm	118.11	in.

Endless instructions

Hot splicing is always preferable. Cold splicing can only be done when the belt is exposed to normal temperatures and the humidity is not excessive. For the working method, consult the splice information and the equipment literature. Apply the recommended splice as indicated in the separate information.

Additional information

The information applies at approx. 20°C (68°F). Keep the belt tension to a minimum for maximum belt and conveyor life. Stated is the belt temperature. The allowable product temperature may vary.

The pulley diameters are valid for a hot spliced belt and at the indicated belt force. Depending on the splice and working conditions (e.g. temperature), different pulley diameters may be possible or necessary. When fasteners are used the minimum diameters are increased by approx. 50%.

Consult our specialists for available profiles and accessories.

Because of continuous development, the presented data is subject to alteration. This data replaces that included in previous publications. Ammeraal Beltech excludes any liability for the incorrect use of the above stated information. Subject to the general terms and conditions of sale and delivery, as applied by its operating companies, are all activities performed and services rendered by Ammeraal Beltech.

Food Statement FDA



Introduction

The Food and Drug Administration (hereafter called *FDA*) of the Public Health Service of the Department of Health, Education and Welfare, established in Washington DC 20204, United States of America, is the world's best known authority involved in consumer protection in respect of potential detrimental influences, which could be caused by any inclusion of substances or ingredients of an unacceptable nature in foodstuffs and confectionery. The *FDA* have prepared a review 'Title 21: Code of Federal Regulations' in respect of their approval of the raw materials in a processed or finished state, and also specified the conditions under which the approval is valid.



Statement

Ammeraal Beltech herewith declares that the cover of the following belt type meets the requirements mentioned in Title 21: Code of Federal Regulations, issued by the *FDA*

Article code Belt construction

» 589711 Nonex EM 10/2 00 + A18 white AS FG

According to paragraph:

- 175.300 (resinous and polymeric coatings)
- 178.2010 (antioxidants and/or stabilizers for polymers)
- 178.3740 (plasticizers in polymeric substances)

for all wrapped and unwrapped foodstuffs

Issue date
January 2022

Head office Ammeraal Beltech Group
Marconistraat 15, 1704 RH Heerhugowaard
P.O. Box 38, 1700 AA Heerhugowaard
The Netherlands